

Cold Lab Chamber / Refrigerator 저온 냉장 챔버 / 정밀형 냉장고

배송비 별도

Cat. No.	Model	Capacity	Temp. Range	EA Price ₩
C07-02-030	LR-CL185	700 L	0 ~ 10℃	3,827,000
C07-02-040	LR-CL212	1200 L		4,748,000

- 0.01℃ 정밀 제어 구현
- Dual 냉각 시스템을 적용하여 제상 불필요.
- 내부 순환 Fan을 통한 정밀한 온도 분포도
- Door Open시 Fan 정지 기능, 온도 변화 최소화
- Pair Glass Door, 성애 발생 억제
- LED Lamp를 장착하여 내부관찰 용이
- Graphic LCD Display, 간편하고 직관적인 Controller 조작
- Auto-tuning, Temperature Calibration 기능
- Automatical Fault Sensing System 기기 스스로 이상 상황을 감시 (특허 등록)
- 레코더를 장착하여 온도 체크 가능 (Option)
- 온도편차 알람 기능
- 정전 보상 기능
- Auto Remote Alarm. 알람 발생시 문자나 전화 발송 (Option)
- Validation Service (IQ, OQ, PQ)
- **PL Insurance** (제조물 배상 책임 보험)
- LK Labkorea

Validation Service


Cat. No.	Model	Description	EA Price ₩
C07-91-999	VA-CLC100	Validation for Cold Lab Chamber	

- 당사 기본 양식에 따른 IQ/OQ Validation Service 비용이며, 고객 요청에 의하여 비용이 변경 될 수 있음

Optional Accessory

Cat. No.	Model	Description	EA Price ₩
C07-02-510	TR2002	Compact Paper Recorder	520,000
C07-91-090	RMAL01	Auto Remote Alarm	650,000
C07-02-044	LR-CLSH01	Shelf for LR-CL185	58,000
C07-02-047	LR-CLSH02	Shelf for LR-CL212	65,000

Cat. No.		C07-02-030	C07-02-040
Model		LR-CL185	LR-CL212
Capacity		700 L	1200 L
Controller	Control	Digital Control	
	Display	GLCD (Graphic LCD)	
	Resolution	0.01℃	
Temperature	Range	0 ~ +10℃	
	Accuracy at 4℃	±0.3℃	
	Uniformity at 4℃	±1.45℃	±1.89℃
Size (w×d×h)	Interior (mm)	700×700×1400	1200×700×1400
	Exterior (mm)	860×1000×1990	1350×1000×2000
Electric Supply	Power	1 Phase, 220 Vac, 60 Hz	
	Max Consumption	1 kW (4.6 A)	1.5 kW (6.8 A)
	Power Line	Standard Plug	
Material	Interior	Stainless Steel 304	
	Exterior	Powder Coated Steel	
Other	Door	One Door	Two Door
	Wire Shelf	4ea	8ea
	Lamp	LED Lamp × 1ea	
	Caster	Leveling Caster	
Safety		Current Protection, Automatical Fault Sensing System	



Epoxy Coated Wire Shelf



Paper Recorder