

Constant Temperature Chamber

하온 챔버

배송비 별도

Cat. No.	Model	Capacity	Temp. Range	EA Price ₩
C07-02-300	LI-CTC501P	150 L	-40 ~ +180℃	8,505,000
C07-02-315	LI-CTC605P	250 L		10,248,000
C07-02-320	LI-CTC705P	500 L		11,765,000

- Program Touch Screen Controller
- 가열 속도와 냉각 속도가 빠름, 온도 환경 테스트에 적합
- Max 120 Pattern / 1200 Segment 프로그램 설정 가능
- 운전중 온도 그래프 표시 기능
- SD메모리 카드를 통한 외부 메모리 지원
- Cable Port 장착, 편리한 테스트 환경 제공
- 내부관찰용 Pair Glass와 LED Lamp 장착
- Door Open시 Fan 정지 기능, 온도 변화 최소화 및 사용자의 안정성 고려
- 레코더를 장착하여 온도 체크 가능 (Option)
- 온도편차 알람 기능
- 정전 보상기능
- Auto-tuning, Temperature Calibration 기능
- 2중화 과온 안전장치, 1차 Controller 과온 Alarm과 2차 과온 차단 회로
- Sign Tower Lamp 장착 가능 (Option)
- Validation Service (IQ, OQ, PQ)
- **PL Insurance (제조물 배상 책임 보험)**
- LK Labkorea

Validation Service

Cat. No.	Model	Description	EA Price ₩
C07-91-977	VA-TC100	Validation for Constant Temp. Chamber	

- 당사 기본 양식에 따른 IQ/OQ Validation Service 비용이며, 고객 요청에 의하여 비용이 변경 될 수 있음

Optional Accessory


Cat. No.	Model	Description	EA Price ₩
C07-02-500	TRL-6	Paper Recorder	1,701,000
C07-02-341	LI-CTCSH01	Shelf for 150 L (LI-CTC501P)	76,000
C07-02-343	LI-CTCSH02	Shelf for 250 L (LI-CTC605P)	82,000
C07-02-344	LI-CTCSH04	Shelf for 500 L (LI-CTC730P)	88,000
O01-96-100	SI300	Sign Tower Lamp	199,000



Program Temp. Controller



Cable Port



Wire Shelf



SI300

Cat. No.	C07-02-300	C07-02-315	C07-02-320
Model	LI-CTC501P	LI-CTC605P	LI-CTC705P
Capacity	150 L	250 L	500 L
Controller	Program Touch Screen Control		
	5.7" Color LCD		
	0.01℃		
Temperature	Range		
	-40 ~ +180℃		
	Accuracy at 50℃		
Size	±0.3℃		
	Uniformity at 50℃		
	±0.82℃	±1.13℃	±1.88℃
Material	Interior	w500×d500×h600 mm	w600×d650×h650 mm
	Exterior	w670×d960×h1630 mm	w770×d1110×h1780 mm
Electric Supply	Stainless Steel 304		
	Powder Coated Steel		
Other	Power		
	1 Phase / 220VAC / 60 Hz		
	Max Consumption	4 Kw (18.2 A)	5 kW (22.8 A)
Safety	Power Line		
	Industrial Plug		
	Wire Shelf	2 ea	3 ea
Safety	Cable Port		
	Ø60 mm × 1ea		
	Caster		
	Leveling Caster (10 mm)		
Safety	Over Temp. & Current Protection, Emergency switch		